



PORTABLE CORDS	TYPE SJ - 300 VOLTS RUBBER JACKETED 60C – CSA/UL
-----------------------	--

POWERsonic Number	No. Of Conds.	AWG Size	Stranding	NOM. INS.	NOM. O.D.	Weight KG/KM	Current Amps.
P33182	2	18	16/30	.030	0.295	89	10
P33183	3	18	16/30	.030	0.320	95	10
P33184	4	18	16/30	.030	0.355	122	7
P33162	2	16	26/30	.030	0.320	107	13
P33163	3	16	26/30	.030	0.345	125	13
P33164	4	16	26/30	.030	0.385	152	10
P33142	2	14	41/30	.030	0.350	113	18
P33143	3	14	41/30	.030	0.380	155	18
P33144	4	14	41/30	.030	0.415	185	15
P33122	2	12	65/30	.030	0.425	205	25
P33123	3	12	65/30	.030	0.450	257	25
P33124	4	12	65/30	.030	0.500	318	20

Description: 18 through 10 AWG fully annealed stranded bare copper per ASTM B-i 74. Premium grade color coded SBR Rubber.

Voltage: 300 Volts

Temp: 60°C

Application: Portable tools and equipment, Portable appliances, Small Motors and associated machinery.

Approvals: UL Flexible