

<b>DIESEL LOCOMOTIVE CABLE</b>	TYPE DLO - THERMOSET JACKETED 90°C to — 40°C — 2000 VOLTS
--------------------------------	---

<b>POWERsonic Number</b>	<b>No. Of Conds.</b>	<b>AWG Size</b>	<b>Stranding</b>	<b>NOM. INS.</b>	<b>NOM. O.D.</b>	<b>Weight KG/KM</b>	<b>Current Amps.</b>
P47000	1	10	27	0.045	0.253	92	55
P470008	1	8	37	0.045	0.270	132	83
P470006	1	6	61	0.060	0.360	208	109
P470004	1	4	105	0.060	0.424	301	145
P470002	1	2	154	0.060	0.509	418	192
P470001	1	1	224	0.060	0.650	641	223
P47010	1	1/0	280	0.080	0.674	752	258
P47020	1	2/0	329	0.080	0.714	881	298
P47030	1	3/0	456	0.080	0.819	1140	345
P47040	1	4/0	551	0.080	0.844	1458	400
P47262	1	262	650	0.095	0.944	1646	458
P47313	1	313	777	0.095	1.024	1869	514
P47373	1	373	925	0.095	1.079	2265	574
P47444	1	444	1100	0.094	1.154	2676	642
P47535	1	535	1332	0.120	1.356	3165	725
P47646	1	646	1600	0.110	1.404	3765	815
P47777	1	777	1925	0.110	1.474	4539	910
P47929	1	929	2300	0.110	1.580	5432	989
P47111	1	1111	2750	0.125	1.140	6273	1076

Description: Stranded tinned copper, separator, EPR insulation, Hypalon jacket

Voltage: 2,000 Volts

Temp: 90°C

Application:

- Diesel electrical locomotives
- Oil and gas drilling rigs
- Mining and earth moving equipment
- Shipyards
- Motor leads
- Portable power supply

Approvals: CSA and UL listed. 4/0 AWG and larger meets IEEE 383